

# Wide Format Laminators Series



ECA-1600Z



WH-1600



SH-1600L



SH-1600

**Lamichina Co. Ltd.**  
[www.lamichina.com](http://www.lamichina.com)



# EC Series Cold Laminators

The entry level electric cold laminator with double sides pressure adjustment, it can meet your basic function requirements!

## Features

- ◎ Large silicon roller for best result of lamination
- ◎ Both manual and electrical operation
- ◎ Variable speed for different works
- ◎ Foot switch
- ◎ Safety, reliable and efficient



EC-670



EC-1600

## Technical specifications

Model	EC-670	EC-1400	EC-1600	EC-1800
Approx laminating speed (m/min)	1~4.8		0~3	
Maximum width (mm)	670	1400	1600	1400
Mounting thickness (mm)	Up to 10mm	Up to 15mm		
Roller diameter (mm)	Upper rollerφ65	Upper rollerφ130		
Speed control	9 grade speed adjustment with reverse function			
Pressure adjustment	Manual			
Power supply AC(V-Hz)	AC 100V; 110V; 220-240V, 50/60Hz			
Power consumption (W)	30	30	50	50
Control system	8-bit micro-processor			
Dimension (mm) with stand	850×300×340	1500×400×400	1800×400×400	2000×400×400
Weight (kg)	25	80	110	130

# EC-Z/ECA-Z Series Cold Laminators

Entry level cold machine, with single side pressure regulation. With or without heat-assistant function. It has economic cost but can finish most of your cold laminating and mounting jobs!

## Features

- ◎ Upper roller can be elevated by 20mm
- ◎ Adjustable speed up to 5m/min
- ◎ Handy reverse mechanism
- ◎ Foot pedal for controlled operation
- ◎ Single side pressure regulation
- ◎ Back paper take-up
- ◎ Optional Heat assistant up to 50 (°C)
- ◎ Multi-safety protection
- ◎ Feeding table guide for both flat lamination and protection



EM-720



ECA-1600Z

## Technical specifications

Model	EM-720	EC-1400Z	ECA-1400Z	EC-1600Z	ECA-1600Z
Approx laminating speed (m/min)	0~3		0~5		
Maximum width (mm)	720	1400	1400	1600	1600
Mounting thickness (mm)	Up to 20mm				
Roller diameter (mm)	Upper rollerφ60	Upper rollerφ130		Lower rollerφ105	
Heat assistant	None	None	50 °C	None	50 °C
Speed control	9 grade speed adjustment with reverse function				
Pressure adjustment	Manually one side pressure adjustment				
Power supply AC(V-Hz)	AC 100V; 110V; 220-240V, 50/60Hz				
Power consumption (W)	50	110	1450	110	1650
Control system	8-bit micro-processor				
Dimension (mm) with stand	850×300×340	1780×561×519	1780×561×519	1986×561×519	1986×561×519
Weight (kg)	25	135	140	150	160

# SH-1600

## Top heat roll laminator

With full independent temperature and speed control, the SH-1600L is ideal for both new and experienced image finishers who require a highly capable laminator but have no need for hot encapsulation.

### Features

- ◎ Solid structure, multi-functions
- ◎ 140mm large silicone rollers
- ◎ Top roller heat up to 120 °C
- ◎ Infrared sensor for precise temperature control
- ◎ Fold away front table
- ◎ Swing out supply shafts for easy loading
- ◎ Self-checking photo cells for safety protection
- ◎ Auto grip shafts for user friendly
- ◎ Laminated graphic rewind



### Technical specifications

- ◎ Max. laminating width: 1600mm
- ◎ Max. laminating thickness: 50mm
- ◎ Max. laminating speed: 6m/min
- ◎ Max. working temperature: 120 °C
- ◎ Top roller lifting: Single hand wheel lift up
- ◎ Heating method: Infrared heating
- ◎ Power requirement: AC 220-240V; 50/60Hz
- ◎ Power consumption: 2700W
- ◎ Packing Dimensions (LxWxH): 2210x710x1473mm
- ◎ Gross Weight: 410 kg



Threading Diagram

# WH-1600

## Wide Format Laminiator



**Lamichina Co. Ltd.**  
[www.lamichina.com](http://www.lamichina.com)



## Heat assistant roll laminator

The WH-1600 is a fully automatic roll laminator with electric take-up and rewind system, it is ideal for both new and experienced image finishers who require a highly capable laminator but have no need for hot encapsulation.

### Features


- ⊙ Automatic laminator, multi-functions
- ⊙ Heat assistant up to 60 °C
- ⊙ Infrared sensor for precise temperature control
- ⊙ Swing out supply shafts for easy loading
- ⊙ Self-checking photo cells for safety protection
- ⊙ Auto grip shafts for user friendly
- ⊙ Laminated graphic rewind

### Technical specifications


- ⊙ Max. laminating width: 1600mm
- ⊙ Max. laminating thickness: 20mm
- ⊙ Max. laminating speed: 6m/min
- ⊙ Top roller temperature: 60 °C
- ⊙ Top roller lifting: Single hand wheel lift up
- ⊙ Heating method: Infrared heating
- ⊙ Power requirement: AC 220-240V; 50/60Hz
- ⊙ Power consumption: 1650W
- ⊙ Machine Dimensions : 2012x442x1190mm
- ⊙ Machine Weight: 145 kg
- ⊙ Stand weight: 37 kg



Control Panel



Sideview



Threading Diagram

Lamichina®  
All for print finishing

# SH-1600L

## Top heat roll laminator



**Lamichina Co. Ltd.**  
[www.lamichina.com](http://www.lamichina.com)





# Top Heat Roll Laminator

With full independent temperature and speed control, the SH-1600L is ideal for both new and experienced image finishers who require a highly capable laminator but have no need for hot encapsulation.

## Features


- ◎ Solid structure, multi-functions
- ◎ 140mm large silicone rollers
- ◎ Top roller heat up to 120 °C
- ◎ Infrared sensor for precise temperature control
- ◎ Fold away front table
- ◎ Swing out supply shafts for easy loading
- ◎ Self-checking photo cells for safety protection
- ◎ Auto grip shafts for user friendly
- ◎ Laminated graphic rewind

## Technical specifications

- ◎ Max. laminating width: 1600mm
- ◎ Max. laminating thickness: 50mm
- ◎ Max. laminating speed: 6m/min
- ◎ Max. working temperature: 120 °C
- ◎ Top roller lifting: Single hand wheel lift up
- ◎ Heating method: Infrared heating
- ◎ Power requirement: AC 220-240V; 50/60Hz
- ◎ Power consumption: 2700W
- ◎ Machine Dimensions (LxWxH): 2100x600x1210mm
- ◎ Gross Weight: 325 kg



Control Panel



Threading Diagram



Backside View